Near-real-time Satellite Cloud Products For Icing Detection And Aviation Weather Over The USA

Patrick Minnis, William L. Smith, Jr., Louis Nguyen
Atmospheric Sciences
NASA Langley Research Center, Hampton, VA

Patrick Heck & Mandy Khaiyer

AS&M, Inc., Hampton, VA



Acknowledgements

• John Murray, ASAP/AVSP NASA LaRC

• Tom Ratvasky and NASA Glenn Twin Otter Icing Team



OBJECTIVES

• Develop a satellite-based icing detection methodology that can be applied operationally with results provided in a timely manner as part of an integrated icing product for the aviation community

• The satellite data to provide near-real time cloud-top & base altitudes for aviation weather applications



OUTLINE

DESCRIPTION OF METHODOLOGY AND CLOUD PRODUCTS

(Minnis)

•RELATING AIRCRAFT ICING TO SATELLITE CLOUD PARAMETERS

(Smith)

• DEMONSTRATION OF PROTOTYPE PRODUCT

(Minnis)



APPROACH

- Use cloud properties currently being derived from satellite data at various time and space scales and relate them to aircraft icing
 - -Developed & applied algorithms to various satellite (GOES, AVHRR, etc.) data for field programs for climate research
 - Currently deriving global cloud and radiation parameters from EOS sensors for global change studies as part of the Clouds and Earth's Radiant Energy System (CERES) Experiment post processing
 - Applying similar algorithms to 4-km GOES data to derive cloud and radiation parameters for DOE ARM program over SGP, for NASA CRYSTAL(FL), Icing (Midwest) running experimentally in R/T



PIXEL-LEVEL CLOUD PROPERTIES

EFFECTIVE RADIATING TEMP Tc **EFFECTIVE HEIGHT, PRESSURE** Zc, pc **TOP PRESSURE, HEIGHT** p_{t}, z_{t} **THICKNESS** h **EMISSIVITY** PHASE (water or ice; 1 or 2) P WATER DROPLET EFFECTIVE RADIUS re **OPTICAL DEPTH** LIQUID WATER PATH **LWP** ICE EFFECTIVE DIAMETER De **ICE WATER PATH IWP**

Blue indicates utility for icing



ICING

ICING CONDITIONS ARE DETERMINED BY CLOUD

• liquid water content, *LWC*

• temperature, *T*(*z*)

droplet size distribution, N(r)

positive w/ intensity negative w/ intensity

r positive w/ intensity

SATELLITE REMOTE SENSING CAN DETERMINE CLOUD

- optical depth, []
- effective droplet size, re
- liquid water path, LWP
- cloud top temperature, *Tc*
- thickness, h

IN CERTAIN CIRCUMSTANCES



CLOUD PRODUCTS VS. ICING PARAMETERS

•
$$LWP = LWC * h$$

•
$$re = f[N(r)]$$

- Tc & h can yield depth of freezing layer
- z_t is top of icing layer
- ceiling = z_t h

IN MANY CASES, SATELLITE REMOTE SENSING SHOULD PROVIDE ICING INFORMATION



DATA

- GOES-8 IMAGER (4KM RESOLUTION) 75° W

Visible $(0.63 \mu \text{m}; \text{ch.1})$ Solar Infrared $(3.9 \mu \text{m}; \text{ch.2})$ IR Window $(10.8 \mu \text{m}; \text{ch.4})$

Split Window (12.0 μ m; ch.5) (G-12: 13.3 μ m)

Visible Channel Calibrated Following Minnis et al. 2002

- Rapid Update Cycle (RUC) 20 km x 20 km hourly analyses
 - surface air temperature => skin temperature
 - temperature & moisture profiles => absorption correction, heights
- CERES clear-sky albedo, surface emissivity (10', 1°)


clear-sky reflectance, brightness temperature => cloud detection/retrieval

- Theoretical cloud reflectance & emittance models

describes angular variation for range of re and □=> cloud detection/retrieval



METHODOLOGY FOR EACH IMAGE TIME





CLOUD MASK

- To detect clouds, the radiances for cloud-free (clear) scene must be known
- Determine clear-sky albedos and surface emissivities after initial processing of data
 - start with CERES values and update
- Use RUC surface temperatures & profiles to estimate clear-sky brightness temperatures
- Must account for angular dependence: bidirectional reflectance models to estimate clear-sky reflectance for each pixel
- Estimate thresholds based on uncertainties in models & spatial/temporal variability of the clear radiances



CLEAR-SKY RADIANCE CHARACTERIZATION

- Predict radiance a given satellite sensor would measure for each channel if no clouds are present
- Estimate uncertainty based on spatial & temporal variability
 & angular model errors
- Develop set of spectral thresholds for each channel
 - Solar, uses reflectance, □
 - IR, use temperature, T

brightness temperature difference, BTD = $T_{\square 1}$ - $T_{\square 2}$ typically, BTD(3.7-11) or BTD(11-12)




CLEAR-SKY REFLECTANCE, SOLAR

- Estimate overhead-sun albedo, $\Box_o = \Box(\mu_o = 1)$ derived empirically with initial runs using CERES VIRS data, then updated for each month using GOES
- Estimate albedo at given local time, $\square(\mu_o) = \square_o \square_o(\mu_o)$ directional reflectance model $\square_o(\mu_o)$ derived for each IGBP type using VIRS
- Estimate reflectance for given viewing angles, $[(\mu_o, \mu, [)] = [(\mu_o)] [(\mu_o, \mu, [)]]$ bidirectional reflectance (BRDF) model [] selected for each surface type from Kriebel (1978), Minnis & Harrison (1984), Suttles et al. (1988)
- Add uncertainty to set reflectance threshold, $\Box_T(\mu_o, \mu, \Box) = \Box + \Box\Box(\mu_o, \mu, \Box)$



PREDICTED CLEAR-SKY & OBSERVED VIS REFLECTANCE & CLOUD MASK 1700 UTC,12/21/00



CLEAR-SKY TEMPERATURE, INFRARED


Estimate surface emissivity, □_s(x,y)

derived empirically with using ISCCP AVHRR DX, VIRS, then Terra MODIS; water & snow theoretical models


- Estimate radiance leaving the surface, $L_s = \Box_s B(T_{skin}) + (1-\Box_s) L_{ad}$ $L_{ad} = downwelling \ atmo \ radiation, \ T_{skin} = skin \ temperature \ from \ model \ / \ obs$
- Estimate TOA brightness temperature, $B(T_{cs}) = (1-\Box_a)L_s + \Box_a L_{au}$ $L_{au} = upwelling \ atmo \ radiation, \ \Box_a = effective \ emissivity \ of \ atmo$ $layer \ absorption \ emission \ computed \ using \ T/RH \ profile, \ correlated \ k-dist$
- Add uncertainty to set T or BTD thresholds, $T_T(\mu) = T_{cs}(\mu) + \Box T(\mu)$
 - reflected solar component included in 3.7-4.0 μm estimate



PREDICTED CLEAR-SKY & OBSERVED IR TEMPERATURE 1700 UTC,12/21/00





PREDICTED CLEAR-SKY & OBSERVED BTD (3.7 - 11) 1700 UTC,12/21/00




STANDARD DAYTIME MASK ALGORITHM

Top Level Daytime Flow Chart






CERES CLOUD MASK 1700 UTC,12/21/00




STANDARD NIGHTTIME MASK ALGORITHM

Top Level Nighttime Flow Chart



CERES CLOUD MASK & BTD(3.7 - 11) REFLECTANCE 0400 UTC,12/01/00



DAYTIME CLOUD RETRIEVALS

- •VISST (Visible, infrared, solar-infrared, split-window technique)
 - physically based method using 0.65, 3.7, 11, & 12 μ m
 - for cloudy pixels, match radiances to model values
- Yields more accurate cloud temperatures than simpler methods
 - adjusts temperature (altitude) of thin clouds
- Provides basis for determining phase
 - in most cases, ice & water models are distinct



Daytime Cloud Property Retrievals

- Derive cloud properties by matching observed radiances to model calculations for water droplets ($2 < r_e < 32 \text{ [m)}$) and ice crystals ($6 < D_e < 135 \text{ [m)}$) through reflectance and emittance parameterizations
- 3.9 \(\square\) m (GOES Channel 2) used for particle size retrieval
- Particle phase determined by:
 - (1) Best available model solution
- (2) $T_{10.8}$ $T_{12.0}$ Difference
- (3) Visible/IR Layer Retrieval
- (4) Retrieved Cloud Temperature




Cloud Tau, phase, r_e (D_e), LWP (IWP), Z_{cld}, T_{cld}




Cloud properties from GOES-8

1815 UTC









Cloud mask & optical depths from GOES-8

1815 UTC









Cloud droplet radius & LWP from GOES-8

1815 UTC








Cloud-top temperature & height from GOES-8

1815 UTC





ARM-Sponsored Comparisons (March 2000)

Comparison of Surface, GOES and Aircraft Results (~10 hours)

